

Anton Koekemoer, Mark Dickinson, and the GOODS Team

Early Results from the Spitzer Space Telescope

Michael Werner

June 7, 2004





- Multi-purpose observatory cooled passively and with liquid-helium for astronomical observations in the infrared
- Launched in August 2003 for a 5+ year mission in solar orbit
- Three instruments use state-of-the-art infrared detector arrays
- Provides a >100 fold increase in infrared capabilities over all previous space missions
- **Completes NASA's Great Observatories**
- Major scientific and technical contributor to NASA's **Origins Theme**
- An observatory for the community. ~600 proposals for General Observer Cycle 1 received and evaluated.

Assembled SIRTF Observatory at Lockheed-Martin, Sunnyvale. **Key Characteristics:** Aperture – 85 cm Wavelength Range - 3-to-180um Telescope Temperature – 5.5K Mass - 870kg Height - 4m





Cutaway View of the Spitzer Space Telescope

-Dust Cover

Solar Panel

Solar Panel Shield

Outer Shell

Cryostat-

Helium Tank -

Spacecraft Shield

Spacecraft Bus-

Cutaway provided by Ball Aerospace

Secondary Mirror
Primary Mirror
Instrument Chamber
Startrackers & Gyros

High Gain Antenna



Spitzer's Instruments and Principal Investigators



IRS


[infrared spectrograph]

J.Houck Cornell

MIPS

[multiband imaging photometer]

G.Rieke Arizona



IRAC

[infrared array camera]

G.Fazio Harvard/ SAO



Assembly of the Heart of the CTA



Telescope Primary Mirror



Cryostat Dome

Lower Portion of Outer Shell



Completion of the Assembly of the Outer Shell







The Spitzer Observatory Fully Assembled








Hoisting the CTA into the Thermal Test Chamber







Spitzer CTA Performance Test Configuration



SPITZER AT THE CAPE









August 25, 2003- WE'RE OFF!










Where's Spitzer Now?

(Mark Garcia, JPL)







Spitzer Cryo-Thermal System – Key Design Features




- High reflectivity shields and shells to minimize heat input to outer shell
 - Aluminized Kapton face sheets on Graphite/composite cores
- Ball Infrared Black paint on anti-solar sun of outer shell
 - Emissivity higher than expected at on-orbit temperature
- Thin, low conductivity cables to minimize conductive heat load
 - Heat sunk and vapor cooled, about 1500 separate conductors and many connectors
- Photon shutter within cryostat stowed before launch to minimize heat load and reduce boil-off before launch. Low emissivity window in aperture door allowed optical tests pre-launch
- GSE cooling loop permitted outer shell temperature to be driven down for ground test
- 360 l. He tank with 49Kg SfHe (93.5% full) at launch; 43Kg at L+60 days
- Two radiation shields within cryostat for ground hold purposes
- Make-up heater within He tank for temperature control
- Very well balanced low thrust vents
- <1mw parastic load on orbit



Spitzer – on orbit heat flow






Flight-Correlated Model December 2003



Helium lifetime tracking 5.8* yr, post-launch, predictions






^{*} Prediction includes 10% operational enhancement



Pulse Method to Enhance Lifetime is Being Successfully Implemented







Spitzer Optical System – Key Features




- 85-cm diameter, all-Beryllium telescope: mass = 55Kg
- One-dimension focus mechanism with throw at focal plane of +/- one inch and step size at focal plane of a few hundred microns
 - Focus criteria and procedures defined and practiced carefully before launch
- Primary mirror tested cold repeatedly and reproducibly. Primary subjected to two "cryo-null" polishing cycles
 - Secondary mirror not separately tested
- Opto-mechanical fiducials on instruments were used to establish confocality of instruments and PCRS after installation and cooldown in cryostat
 - Alignment maintained throughout system buildup via carefully crafted alignment plan
 - Ambient temperature optical tests used to monitor alignment during shipping, etc.
 - Windows in dust cover allowed partial verification of alignment at Cape
- End-end optical test with system cold in Brutus verified image quality, focus position, and confocality
- Light sources in the cold focal plane for ground use only to permit image test by auto-collimation and to monitor instrument aliveness
- Window in aperture door permitted alignment and image quality to be assessed with cryostat outer shell warm.



Predicted Wave Front Error Across the Spitzer Focal Plane





Field Point Predicted On-Orbit Wavefront


Requirement is 0.464 micron, corresponding to 6.5um diffraction limit. On orbit performance is better than 5.5um diffraction limit over IRAC field

	(microns rms)		
0	0.300		
1	0.441		
2	0.314		
3	0.321		
4	0.459		
5	0.371		
6	0.300		
7	0.308		
8	0.426		



Effects of Focussing Spitzer at 3.6um








Surface Plots of the IRAC Oversampled PSFs for all 4 IRAC Channels After Focus







4.5 um

5.8 um

8 um


Figure 2-3. Surface plots of the Drizzle-reconstructed PSFs. Each plot has been normalized to 1.


(Dave Elliott, JPL)



24um Point Spread Functions (K. Stapelfeldt, MIPS/JPL)







Tiny Tim Prediction

On-orbit measured


Fomalhaut



Spitzer Pointing and Control System – Key Design Features



- Very capable 5x5 sq degree autonomous star tracker with NEA~0.11 arcsec when tracking 35 stars
- Redundant Kearfott IRU [gyros] and Ithaco Reaction Wheel Assemblies
- Pointing and Control Reference Sensor [PCRS] Visible wavelength Silicon diode array in cold focal plane to maintain telescope/star tracker boresight alignment
- Peakup arrays in IRS to facilitate placing science targets on spectrograph slits. PCRS can also be used in this fashion.
- Cold N2 gas system used to dump angular momentum accumulated in RWA's
 - Contamination and leaky thursters were a big problem before launch
- Solar system target tracking at rates in excess of 0.1 arcsec/sec






On-orbit Pointing System Performance preliminary assessment



Parameter	Requirement	Actual	Units	
Stability over 200 s	0."3	003	1σ radial, rms	
Stability over $600 \mathrm{s}$	06	003	1σ radial, rms	
Blind pointing	5"	$1\rlap.{''}4$ [sometimes $<1\rlap.{''}]$	1σ radial	
Offset pointing $(<30')$	2'' [QP]	OK	1σ radial	
	1'' [HP2]	OK (maybe even point & shoot)		
	0."4 [HP1]	Not finished yet. Short-term gyro drift is the issue. Alignment good. Handoff time can be but has not yet been optimized.		
Moving object tracking	$\leq 1''/\mathrm{s}$	OK so far, up to $200''/hr$		
PCRS	0.14 over $2''$	Better close, worse further out		
Star tracker accuracy	06	02	1σ per axis	
NEA	022	0."106-0."117		
rotation NEA	62	2.5		
Focal plane survey	various	IRAC & IRS OK with margin. MIPS TBD		

- Star trackers better than expected; gyros worse. Handoff time will be adjusted.
- Overall, very good. Areas being worked will not interfere with science.



100.00%

90.00%


Infrared Mosaic of Nearby Galaxies

Spitzer Space Telescope • IRAC

M. A. Pahre & G. G. Fazio (SAO) / NASA / JPL-Cattech


sao-2004 -19

Dissecting a Nearby Galaxy M81 – Spitzer 3.5 to 24μm Composite




RCW49 – GLIMPSE Image Candidate Protostars circled 000

GOODS CDF-S IRAC 4.5 µm Feb. 2004 23 hours/point 10 x 10 arcmin



Spitzer Looks Back in Time and Space

 $3.6 \ \mu m$ $4.5 \ \mu m$



z=5.8 galaxy


5.8 µm




Spitzer Space Telescope Reflection Nebula NGC7023 — Visible and IRAC Images



(K.Gordon, MIPS/Arizona & M.Marengo, IRAC/SAO)








Spitzer Spectra of T Tauri stars (Forrest, Watson et al)



CoKu Tau 4
spectrum shows
evidence of
central clearing,
perhaps due to
formation of a
planet about 6au
from the star.





Recent and Upcoming Science Milestones



- Spitzer data archive opened, mid-May
- Results of first GO selection announced 28 May
- Denver AAS Meeting 31 May 3 June
 - Special Spitzer Session all day on Tuesday 2 June
 - Numerous Spitzer related press releases, including joint Spitzer-Hubble release on GOODS results
- First Spitzer papers posted on SSC website and Astro-Ph starting June 1
- [You are here!]
- Special Spitzer issue of Astrophysical Journal Supplements, September 1
- First Spitzer Science conference, Pasadena, November 9-12.
- Cycle 2 Call for proposals issued November 2004, due February, 2005
 - We invite you to share the excitement of Spitzer!




The SIRTF Science Working Group. First Meeting, Summer, 1984

Dale Cruikshank Giovanni Fazio Bob Gehrz

Jim Houck Mike Jura Charles Lawrence

George Rieke Frank Low Marcia Rieke

Tom Roellig Tom Soifer Mike Werner Ned Wright




The Spitzer Space Telescope Mission


A Report to the American Astronomical Society

Michael Werner

Spitzer Space Telescope Project Scientist Jet Propulsion Laboratory/Caltech June 1, 2004

[SSC.spitzer.caltech.edu]








Spitzer: Promise Fulfilled!!



"The highest priority for a major new program in space-based astronomy is the Space Infrared Telescope Facility (SIRTF)."

National Research Council, Astronomy and Astrophysics Survey Committee, 1991



"SIRTF remains unparalleled in its potential for addressing the major questions of modern astrophysics."

> National Research Council, Committee on Astronomy and Astrophysics, 1994

"Taken together, the projects we recommend represent an exciting use of NASA's next major astrophysical observatory. Each of the projects will yield superb science that we expect of a major investment of time in a NASA Great Observatory. A hallmark of each of these projects is that they fully exploit the unique and special capabilities of SIRTF that make it a major NASA mission and the highest priority space project of the 1991 National Academy of Sciences Decade Review."

Letter from SIRTF Legacy Science TAC Chair John Bahcall to SSC Director Tom Soifer, November 2000